

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 February 2005 (24.02.2005)

PCT

(10) International Publication Number
WO 2005/016579 A1

(51) International Patent Classification⁷: **B22D 17/04**,
35/04

(74) Agent: **PHILLIPS ORMONDE & FITZPATRICK**; 367
Collins Street, Melbourne, VIC 3000 (AU).

(21) International Application Number:
PCT/AU2004/001096

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(22) International Filing Date: 16 August 2004 (16.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003904394 15 August 2003 (15.08.2003) AU

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (for all designated States except US): **COM-
MONWEALTH SCIENTIFIC AND INDUSTRIAL
RESEARCH ORGANISATION** [AU/AU]; Limestone
Avenue, Campbell, ACT 2612 (AU).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **FINNIN, Barrie,
Robert** [AU/AU]; 36 Gloucester Road, Ashburton, VIC
3147 (AU).

Published:

— with international search report

[Continued on next page]

(54) Title: FLOW SYSTEM FOR PRESSURE CASTING



(57) Abstract: A metal flow device, for high pressure die casting of alloys using a method or machine having, or operable to provide, a pressurised source of molten alloy and a mould defining at least one die cavity, defines a metal flow path by which alloy received from the pressurised source is able to flow into the die cavity. A first part of the length of the flow path includes or comprises a runner; while a second part of the length of the flow path from an outlet end of the runner includes a flow-path exit module (FEM). The FEM has a form which controls the alloy flow whereby the alloy flow velocity decreases progressively from the level at the outlet end of the runner whereby, at a location at which the flow path communicates with the die cavity, the alloy flow velocity is at a level significantly below the level at the outlet end of the runner and such that, on filling of the die cavity, the alloy is able to undergo solidification in the die cavity and back along the flow path towards the runner.

BEST AVAILABLE COPY

WO 2005/016579 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

BEST AVAILABLE COPY